

Performance you can trust

Spatter Release Spray

Product Overview

Spatter Release Spray has been formulated to prevent adhesion of spatter to jigs, fixtures, shrouds and workpiece during the welding process.

Spatter Release Spray can be easily removed by wiping with a cloth saving time and money.

Benefits

- Heat resistant barrier film that prevents the adhesion of weld spatter
- Non silicone—does not affect subsequent galvanizing or paint operations
- Will not interfere with weld formation.
- Non Corrosive
- Suitable for all general welding processes

Directions for Storage and Use

- Shake aerosol well before use
- Apply an even film from a distance of 20-25cm
- As with all products of this type it is recommended that compatibility with painted or coated surfaces, plastics and rubber be tested prior to use
- The storage temperature should be kept below +50°C, and the storage area should be out of direct sunlight
- Shelf life is 5 years from date of manufacture

Pack Sizes

For pack sizes and part codes please visit:
www.rocol.com or email:
customer.service@rocol.com

T +44 (0) 113 232 2600
F +44 (0) 113 232 2740
E customer.service@rocol.com
www.rocol.com

ROCOL House, Swillington, Leeds, LS26 8BS

Registered Company No 559693 VAT No 742 0531 67
Registered Office: Nexus House, Station Road, Egham, Surrey, TW20 9LB

ROCOL A division of *ITW* Ltd





Performance you can trust

Spatter Release Spray

Property	Spatter Release Spray
Odour	Characteristic
Flammability	Non flammable
Solvent	Chlorinated
Propellant	CO ₂
Storage	Storage temperature should be kept below 50°C.
Shelf life	5 years

Values quoted above are typical and do not constitute a specification.

Safety Data Sheets

Safety data sheet sheets are available for download from our website www.rocol.com or may be obtained from your usual ROCOL contact.

The information in this publication is based on our experiences and report from customers. There are many factors out of our control or knowledge which affects the use of our products, for which reason it is given without responsibility.

Issue:3 Date 08-19

T +44 (0) 113 232 2600
F +44 (0) 113 232 2740
E customer.service@rocol.com
www.rocol.com

ROCOL House, Swillington, Leeds, LS26 8BS

Registered Company No 559693 VAT No 742 0531 67
Registered Office: Nexus House, Station Road, Egham, Surrey, TW20 9LB

ROCOL A division of *ITW* Ltd

